



**fitted with**

**work equipment**  
**connected load**  
**power consumption**  
**power factor**  
**luminous flux**  
**luminous efficacy**  
**light distribution**  
**direct ratio**  
**light colour**  
**color rendering index (CRI)**

**glare-free**  
**luminance**  
**unified glare rating**  
**technology**  
**usage**  
**luminaire body**  
**lamp cover**  
**tubular section**  
**luminaire base**  
**weight (net)**  
**mains lead**

**fastening**  
**decorative contrast side parts**  
**special features**

3 x LED module  
 light colour adjustable white  
 Energy efficiency category A  
 2 x LED module  
 light colour neutral white  
 Energy efficiency category A+  
 power supply unit  
 220-240V; 50/60Hz  
 approx. 94 W  
 approx. 0,966  
 approx. 11500 lm  
 approx. 122 lm/W  
 direct/indirect  
 approx. 17 %  
 adjustable white  
 > 80  
 conical prismatic screen  
 < 2800 cd/m<sup>2</sup>  
 < 16  
 controlled depending on presence and daylight  
 multi-function switch  
 steel/plastic, painted, white  
 polycarbonate, clear  
 steel tube, painted, tubular section upright, white  
 C-form flat  
 approx. 18.5 kg  
 approx. 3,0 m; mains plug  
 CEE 7/II  
 table adaptor  
 flint grey  
 luminaire head detachable, integrated light- and  
 presence-detecting sensor PULSE, integrated light  
 management for biodynamic light PULSE VTL, light forming,  
 retrofit with EnOcean wireless module PULSE-TALK



CEE 7/II

**luminous intensity**

